



**POLYURETHANE**  
MACHINERY CORPORATION

# PREMIER X

HYDRAULIC PROPORTIONER FOR  
POLYUREA COATING APPLICATIONS

**PREMIER X** is the most technologically advanced high pressure proportioner in the PMC lineup.

**PREMIER X** puts you in complete control with intuitive design and remote capabilities

Ideal for use in high output coating applications.

PMC RELIABILITY MEETS THE FUTURE OF  
PLURAL COMPONENT PROPORTIONERS

## KEY FEATURES:

- Output of **2.8 gal./min.** and **3500 psi**
- User management and traceability features
- Intuitive **Touchscreen dashboard** - all controls at your fingertips
- Chemical Management display insures that ratio, temperature and pressures are accurate
- Reporting software captures **data in real time** and can email daily reports
- Saves all historical data and alarms
- On-screen technical support
- Web enabled for **Remote Access** anywhere there is a signal



[WWW.POLYMAC-USA.COM](http://WWW.POLYMAC-USA.COM)



**BUY THE BEST THE FIRST TIME**

**WORLDWIDE HEADQUARTERS**  
One Komo Drive Lakewood, NJ 08701  
P: (732) 415-4400 | E: [marketing@polymacusa.com](mailto:marketing@polymacusa.com)



POLYURETHANE  
MACHINERY CORPORATION

# PREMIER X

## Premier X High Pressure Proportioner

for high output coatings applications such as waterproofing, decking and protective liners.

**Remote access** the proportioner from any web enabled device without the need to download an app.

On-screen **Technical Support View** displays raw data to help diagnose issues.

## Chemical Management

**Display** ensures that ratio, temperature and pressures are accurate on both sides.

**Reporting Software** captures data in real time and displays a graph for easy-to-see results. Reports can be emailed directly from the machine.



## TECHNICAL DATA

### MODEL Premier X

Output.....	2.8 gal./min (10.59 lt/min)
Max. Working Pressure.....	3500 psi (241 bars)
Max. Hose Length.....	410 ft. (125 m)
Heater Wattage .....	21,000 watts
Hose Heating Power .....	120 V
Max. Fluid Temp .....	190 °F (87.7 °C)
Weight (Empty Hydraulic Tank) ..	670 lbs (304 kg)
Weight (Full Hydraulic Tank).....	844 lbs (383 kg)
Electrical @ 18KW Heaters .....	83 A-18,000 W htr.
Dimensions (W x D x H) .....	40in x 30in x 55in (102cm x 76cm x 140cm)



## ORDERING INFORMATION

Part #...Description

### PREMIER X

203716....PRMRX,5HP,220V,3PH,RV,120T,21K

\*Output measured with mineral oil

## PMC LEGEND FOR MACHINE DESCRIPTIONS

**PH-2**...Machine Series

**3HP**....Horsepower (3hp, 5hp, 7.5 hp)

**230V**...Voltage (230v, 380v or 460v)

**1PH**....Phase (Single or Three)

**RV**.....Recirculation Values

**90T**....Transformer Size (30V, 70V, 90V, 120V)

**10KW**....Heater Wattage

**1M**.....Inlet Monitoring

**PCB**.....Pressure Balance Control

**DURABLE. RELIABLE. SMARTER.**  
OUR PRODUCTS OUTPERFORM & OUTLAST OUR COMPETITORS

BUY THE BEST  
THE FIRST TIME  
FIND A →  
DISTRIBUTOR



**POLYMAC-USA.COM**